

**XARIOS 350** is a direct drive refrigeration unit specifically designed for the transportation of fresh or frozen goods in medium-sized delivery vehicles with box volumes up to 32 m<sup>3</sup>.

With a sleek new aesthetic design and an extra-flat evaporator that allows loading up to 200 mm from the top, XARIOS 350 gives unrivalled performance and reliability for vehicles in an urban distribution environment.

- ▶ Optimum performance for superior cargo protection
- ▶ Extremely high capacity airflow for constant quality and freshness throughout the box
- ▶ Unrivalled temperature recovery for urban distribution
- ▶ Microprocessor control and cab command make operation easier and safer



- ▶ Rapid installation and easy servicing contribute to reduced life cycle cost
- ▶ Innovations that respect the environment.

## S model

- ◆ Refrigerant HFC R404A
- ◆ Multi-function cab command
- ◆ Extra-flat evaporator
- ◆ Hot gas defrost system
- ◆ Standby & road operation hourmeters
- ◆ Operation on 12VDC and 24VDC vehicles
- ◆ Liquid injection for high ambients
- ◆ Road or Road & Standby operation

### Electrical features:

- ◆ Standby compressor TM15
- ◆ Remote plug (Road & Standby version)
- ◆ Single or 3-phase operation

### Safety devices:

- ◆ Skin-removal safety mechanism
- ◆ Thermal protection (transformer, diode bridge)
- ◆ Low and high refrigerant pressure protection
- ◆ Secured installation configuration setting

### Command components:

- ◆ Microprocessor control system
- ◆ Automatic and manual defrost
- ◆ Digital display: Temperature in °C or °F, set-point, return air, data, configuration parameters, hourmeters and alarms

## T model: Extra features


- ◆ High capacity hot gas heating system

## Equipment:

- ◆ Road compressor mounting kit
- ◆ Road compressor TM15
- ◆ Electrical kit from 400/3/50 to 230/3/50

## Accessories:

- ◆ Drain water heater for deep frozen application
- ◆ Extension connection set for flexible evaporator positioning
- ◆ Door switch sensor for door openings




## Condenser

Weight:  
Road & Standby: 77 kg  
Road: 40 kg

## Refrigeration capacity (road)

0 °C / + 30 °C: 3310 W  
- 20 °C / + 30 °C: 1900 W  
Ambient temperature at + 30 °C  
(per A.T.P. procedure)

## Airflow: 1540 m<sup>3</sup>/h



## Extra-flat evaporator

Weight: 29 kg

CARRIER TRANSICOLD EUROPE



CARRIER TRANSICOLD EUROPE S.A.

10, boulevard de l'Oise  
F-95031 CERGY PONTOISE CEDEX  
Phone: +33 (0)1 34 43 48 00 - Fax: +33 (0)1 34 43 48 48

450 CARRIER SERVICE STATIONS  
in EUROPE, RUSSIA,  
MIDDLE EAST and AFRICA.

Our company is constantly seeking to improve the quality of its products and, therefore, reserves the right to modify its products without prior notice.

Carrier Transicold Europe - S.A. au capital de 105 547 600 F  
R.C.S. Pontoise B 410 041 776 - Code APE 516 K - VAT: FR52410041776  
The information contained in this document is not contractually binding,  
and may not be reproduced without prior approval - (12-00) 62-61032-20



Carrier

A United Technologies Company